

Kopervet

Product Data Sheet | Art.no 24.113

Description

Copper grease suitable for use in extremely high temperatures up to +1100°C. Provides long-lasting protection against fretting of materials due to corrosion and chemical effect from external influences. Suitable for lubricating headless screws and studs, manifolds, brake components, wheel bolts, battery clamps, etc.



Available in



400g



500g



18kg

Application

Suitable for lubricating ovens, headless screws and studs, manifolds, brake components, wheel bolts, battery clamps, spark plug screw threads, etc.

Instructions for use

Avoid spillages due to excessive grease usage. Seal the packaging properly after use. Do not mix with other types of grease. The safety information sheet for this product is available on request or can be downloaded directly via the website.

Typical standard analyses

Colour	Copper
Soap Type	Calcium
Dropping point, °C	173
Welding load	420 kgf
Copper corrosion	1a
Penetration (worked)	249 mm
NLGI class	3
Temperature range, °C	-20 up to 1100 °C

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms