

Lithium MP EP 3

Product Data Sheet | Art.no 24.120

Description

Universal, extra thick lubrication grease. Suitable for rotating parts, dowel and bushing connections, etc. Offers good resistance to moisture and dust, is waterproof and ensures long-lasting lubrication. Suitable for use at high temperatures and with heavy loads.



Available in



400g



18kg



50kg



185kg

Typical standard analyses

Colour	Brown
Soap Type	Lithium
Base oil type	Mineral
NLGI class	3
Unworked penetration at 25 °C	220 - 250
Dropping point, °C	Min 180 °C
4-ball wear test, Weld load, kg	>250 Kg
Water washout at 80 °C, %	2.0
Copper corrosion	Max 1b
EMCOR corrosion test	1
Temperature range, °C	-20 up to 120

Date printed 14-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms