

Multi Grade Turbo 15W40

Product Data Sheet | Art.no 4A05.01

Description

Modern, multigrade 15W40 engine oil for high-performance, heavy-duty petrol and diesel engines. Also suitable for turbo-engines. Prevents wear and tear and provides optimal engine protection. Usable in all seasons.



Available in



1L



5L



20L



60L



208L



Bulk

Typical standard analyses

Density at 15 °C, kg/l	0,877
Viscosity -20 °C, mPa.s	4070
Viscosity 40 °C, mm ² /s	105,00
Viscosity 100 °C, mm ² /s	14.70
Viscosity Index	145
Flash Point COC, °C	230
Pour Point, °C	-30
Total Base Number, mgKOH/g	10.2
Sulphate Ash, %	1.29

Performance level

ACEA A3/B4-12
API SL/CF
MB 229.1
VW 501.01 / 505.00

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms