

Power Steering Fluid

Product Data Sheet | Art.no 4D3301

Description

Special hydraulic oil with a very high viscosity index for power steering, level control, shock absorbers and such like. Especially suitable for Volkswagen and Mercedes.



Available in



1L



5L



20L

Typical standard analyses

Density at 15 °C, kg/l	0,827
Viscosity -20 °C, mm ² /s	230
Viscosity 40 °C, mm ² /s	18,70
Viscosity 100 °C, mm ² /s	6,00
Viscosity Index	> 300
Flash Point COC, °C	154
Pour Point, °C	-55
Colour	Groen

Performance level

VW TL 52146
MAN M 3289
PSA S712710
MB 345.0
DIN 51524-T3, ISO 7308
Ford M2C204-A
Volvo 1161529
Chrysler MS-11655B
ZF TE-ML 02K

Date printed 15-09-2023

The information shown here is intended to give the reader an impression of the characteristics and possible applications of our products. Although this overview has been compiled with all due care on the date shown, the compiler accepts no liability for loss or damage resulting from omissions or errors in the overview, especially where these result from obvious typing errors. The supplier's terms and conditions of delivery are applicable to all deliveries of these products. Readers are advised to make a final choice in consultation with the supplier, especially for critical applications. An up-to-date safety information sheet for this product is available to download via our website. General Terms and Conditions: www.gvg.nl/terms